



Snack & Food



SNAKKY MAX FOOD





SNAKKY MAX FOOD is capable of dispensing a large number of snacks, and at the same time is fitted with fresh food products disposed on a minimum of 2 till a maximum of 4 trays, which maintain a temperature lower than 4°C, while the three upper trays are reserved to snack products with a temperature between 8° and 15°C.

The Snakky Max Food machine is suitable also for operation under normally adverse environmental conditions.

The anti-condensation system ensures optimum visibility of the products with a maximum external temperature of 32°C and 65% relative humidity.

Furthermore, the anticondensation system also eliminates moisture from the product dispensing compartment.

Thanks to the proper kit it is possible to dispense bread sticks 22.5 to 30 cm long, in addition to the standard triangular sandwiches.



Product-holders with adjustable width

INDICATIVE CONSUMPTION

For each hour of stand-by	266 Wh
Ambient temperature	20°C
Refrigerated box temperature	3,5°C

At the same time, the following can be installed:

- Change-giver coin mechanism/validator
- Bill validator
- Cashless system with key or card

ACCESSORIES

- Kit to block dispensing compartment
- Photocell kit (standard)
- Master/slave kit
- Bidirectional drawer motors kit
- Coin box cover kit
- Wall mounting bracket kit
- RS232 jack kit
- GSM kit

CHARACTERISTICS

Height	1830 mm*
Width	735 mm
Depth	855 mm
Overall depth with door open	1350 mm
Wight	225 kg ca.
Power supply voltage	230 V
Power supply frequency	50 Hz
Installed power	560 W
Refrigerant	R134a
Maximum operating conditions	32°C - 65% u. r.

*+10 - 10 mm

USER INTERFACE

Offering optimum product visibility for easy identification of the items and simple selection, via the numeric keypad.

Is possible to programme the selection numbers of the numeric keypad to allow virtual selections and FIFO selections. FIFO modality allows an uniform emptying of the machine, a frontal machine always full and an optimal temperature of the products.

- Slightly tilted blue alphanumeric display with 4 lines and 20 characters
- Sound signal at the end of the product dispensing sequence
- Ergonomic compartment which opens outward to ensure easy access to the dispensed product - even with one hand.

SAFETY DEVICE

To guarantee the conservation of the products in the food area, a temperature safety block has been included in the software of the machine.

ELECTRONIC CONTROL

- 16-bit electronic control with incorporated Flash EPROM
- Automatic setup and reading of statistics with Flash application or Up-Key
- Remote monitoring via GSM technology (with proper kit)

PAYMENT SYSTEMS

The payment systems and the electronic board are located inside a separate compartment, with independent access and slide-out opening for complete extraction, allowing work to take place in this area without affecting the temperature inside the product compartment.

Snakky Max Food is pre-set for the installation of systems with Executive and MDB protocol, as well as validators.

CONFIGURATION

- 3 snack trays**
15 selections / 156 products
- 3 food trays**
12 selections / 72 products

8	8	8	8	160 mm		
13	13	13	11	11	11	160 mm
10	10	10	10	10	10	178 mm
6	6	6	6	6	6	198 mm
6	6	6	6	6	6	172 mm
6	6	6	6	6	6	172 mm

Legend: Snack Food

The numbers in the table indicate the product capacity

L247U00

N&W Global Vending reserves the right to alter specifications without notice.



N&W GLOBAL VENDING S.p.A.

Via Roma, 24
24030 Valbrembo (BG) Italy
Ph. +39 035 606111 - Fax +39 035 606519

www.nwglobalvending.com